

6" LED Square Cylinder Down Wall Lantern Wall mounted • Wet location listed

Description:

6" LED Square Cylinder with heavy-duty aluminum construction, die-cast aluminum wall bracket. UL listed for wet locations. Powder coat for chipping and fading resistance. Dark Sky compliant for down light only. The P5643 is ideal for indoor/outdoor applications. It can be used in residential or light commercial installations.

Specifications:

- Metallic Gray (-82) (painted)
- Die-cast aluminum Construction
- Ideal for a wide variety of interior and exterior applications.
- Die-cast aluminum construction with durable powder coated finish
- 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1
Input Power	29w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	
Lumens/LPW (Delivered)	1800/60 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cULus Wet location listed
	Meets California Title 24 high efficacy requirements for outdoor use only

P5643-82-30K

Images:



Dimensions:

Width: 6"
 Height: 12"
 H/CTR: 7-1/2"

6" LED Square Cylinder Down Wall Lantern

Wall mounted • Wet location listed

PROGRESS **LED**

P5643-82-30K

Dimming Notes:

P5643 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P

Lutron Nova_T NTELV-300

Lutron Maestro MAELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.